

## Product Data Sheet

### ATF DII

#### Description and Applications

**Saheli ATF D II** is an automatic transmission fluid for automatic transmissions in older vehicles specifying use of DEXRON® II D quality fluids. The high quality base oils and special additive system used in **Saheli ATF D II** provides resistance to oxidation, better frictional properties, good low temperature fluidity, improved seal compatibility and wear protection. **Saheli ATF D II** exceeds the performance requirements of General Motors DEXRON® II D specification and provides excellent driving experience in a variety of driving conditions.

#### Features and Benefits

- Good thermo-oxidative stability that minimizes formation of lacquer, sludge and deposits and keeps transmissions clean, the controlled frictional characteristics helps in consistent and smooth shifts in a variety of driving conditions, improved anti-wear technology protects critical transmission parts against wear.
- Extremely high Viscosity Index ensures adequate lubrication in both high operating and low starting temperatures and better foam control leads to smooth and lasting shift feel and reduces fluid loss.
- Enhanced low temperature fluidity assists in good cold start performance and provides better protection against rust and corrosion. Product compatible with all common seal materials.

#### Applications

**Saheli ATF D II** is recommended for all vehicles of General Motors requiring DEXRON®-II D quality fluids and also recommended for power steering units, certain manual transmissions and hydraulic systems where such type of fluids are required.

#### Specifications

##### GM DEXRON® II D

Test Parameters	Test Method	Typical Results
Density @ 15°C gm/cm <sup>3</sup>	ASTM D4052	0.861
Viscosity Index	ASTM D2270	162
Viscosity @ 100°C (cSt)	ASTM D 7042	7.24 mm <sup>2</sup> /s
Viscosity @ 40°C (cSt)	ASTM D 7042	37.3 mm <sup>2</sup> /s
Brookfield Viscosity @ -40°C	ASTM D 2983	40750 cP
Pour Point °C	ASTM D 97	-39
Flash Point (COC) °C	ASTM D 92	172