

Product Data Sheet

Agro Power HD

Description and Applications

Saheli Agro Power HD series are heavy-duty diesel engine oils developed to meet the requirements of a wide range of diesel engines of tractors and other farm equipments. These oils are formulated from highly refined base stocks and selected additives to provide effective protection to engines operating under moderate to severe conditions. They are available in two viscosity grades viz. **SAE 20W40** and **SAE 40** and exceed the performance requirements of **API CF**.

Features and Benefits

- Suitable for tractors operating under varied weather conditions
- Improved detergency helps reduce deposits and keeps engines cleaner
- Better thermo-oxidative stability protects against sludge build-up, deposits and oil degradation and controls oil thickening
- Effective anti wear properties protect engine components against wear to offer extended engine life and reduced maintenance costs
- Good corrosion inhibition properties protect engine parts against corrosion

Applications

- Diesel engines of tractors and other farm equipments requiring API CF quality oils.
- Also suitable for diesel engines where such quality oils are recommended.

Specifications

Meets:

- **API CF**

Test Parameters	Test Method	Typical Results	
SAE Viscosity Grade		20W40	40
Density @ 15°C gm/cm ³	ASTM D1298	0.892	0.896
Viscosity Index	ASTM D2270	113	96
Viscosity @ 100°C (cSt)	ASTM D 445	14.1	14.2
Pour Point °C	ASTM D 97	-24	-15
Flash Point (COC) °C	ASTM D 92	238	242
Sulphated Ash, %wt	ASTMD 874	1.2	1.2