

# Product Data Sheet

## Ezo 2T

### Description and Applications

**Saheli Ezo 2T** is a high quality lubricant suitable for use in air cooled 2-stroke gasoline engines deployed in variety of applications. It is blended from high quality base stocks and fortified with carefully selected additives to provide engine protection and cleanliness in 2-stroke engines.

The product meets the international specifications of **API TC** and **JASO FB**.

### Features and Benefits

- Excellent lubricity protects against piston scuffing and premature wear of engine components.
- Proven additive technology controls engine and exhaust system deposits.
- Low ash formula prevents pre-ignition and spark plug fouling.
- Easy miscibility with gasoline ensures stable homogeneous mixture even at low ambient temperatures.

### Applications

- Recommended for 2-stroke motorcycles and scooters requiring API TC and JASO FB quality oil
- Suitable for both oil-injection and premix lubrication systems; follow manufacturer's recommendation for oil to fuel ratio.
- Also recommended for 2-stroke engines in other applications requiring this quality oil.

### Specifications

Meets:

- **API TC, JASO FB**

Test Parameters	Test Method	Typical Results
Density @ 15°C gm/cm <sup>3</sup>	ASTM D1298	0.875
Viscosity Index	ASTM D2270	120
Viscosity @ 100°C (cSt)	ASTM D 445	9.15
Pour Point °C	ASTM D 97	-9
Flash Point (COC) °C	ASTM D 92	78
T.B.N mg KOH/gm	ASTM D 2896	0.80
Sulphated Ash, %wt	ASTMD 874	0.09