

# Product Data Sheet

## Ezo 4T Plus

### Description and Applications

**Saheli Ezo 4T Plus** series are premium quality 4-stroke gasoline engine oils developed specifically to meet the special requirements of the latest high performance air cooled 4-stroke motorcycles. These oils are blended from superior quality high viscosity index base oils and specially selected performance additives to provide excellent protection for engine, gearbox and wet clutch used in 4-stroke motorcycles.

**Saheli Ezo 4T Plus** provides high degree of reliability even under severe operating conditions.

**Saheli Ezo 4T Plus** exceeds the requirements of API SL and JASO MA2 for 4-stroke motorcycle oils as well as those of leading global 4-stroke motorcycle manufacturers.

**Saheli Ezo 4T Plus** is available in **SAE 10W30** and **20W40** grades.

### Features and Benefits

- Outstanding thermo-oxidative stability minimizes high temperature deposit formation and controls oil thickening facilitating extended engine and oil life.
- Exceptional anti-wear properties protect vital engine and gear components leading to reduced maintenance costs.
- Optimized frictional properties eliminate wet clutch slippage leading to increased power/fuel economy and improved drivability.
- Unique combination of detergents and dispersants provide excellent control on piston deposits leading to faster heat dissipation and longer engine life.
- Excellent shear stability maintains viscosity under high temperature-high shear environment and provides improved wear protection.
- Exceptional low volatility characteristics reduce oil consumption and hydrocarbon pollution.
- Effective rust and corrosion inhibition property ensures longer life of critical engine components.
- Fuel saving potential (with the grade **SAE 10W30**).

### Applications

- Recommended for new generation 4-stroke Gasoline engines in high performance motorcycles of all leading global manufacturers.

### Specifications

- **API SL, JASO MA2**

Test Parameters	Test Method	Typical Results	
		10W30	20W40
SAE Viscosity Grade		10W30	20W40
Density @ 15°C gm/cm <sup>3</sup>	ASTM D1298	0.892	0.896
Viscosity Index	ASTM D2270	147	112
Viscosity @ 100°C (cSt)	ASTM D 445	11.4	14.50
Pour Point °C	ASTM D 97	-33	-24
Flash Point (COC) °C	ASTM D 92	232	240
Sulphated Ash, %wt	ASTMD 874	0.9	0.91

The information contained in this data sheet are indicative and correspond to the date of publication of this document. The above data are based on laboratory tests. It is the reader's interest to ensure whether the most recent version of the data sheet. A safety data sheet is available on request by our sales consultant. For more information, please contact the sales department.

Saheli Energy Solutions P.O.Box : 500102 Fax : +971 44301710 Dubai, UAE - info@saheli-lubes.com - www.saheli-lubes.com