

Product Data Sheet

Ezo 4T

Description and Applications

Saheli Ezo 4T series is a high quality 4-stroke gasoline engine oil developed specifically to meet the special requirements of air cooled 4-stroke motorcycles. It is blended from highly refined base oils and performance additives to provide protection to engine, gear box and wet clutch used in 4-stroke motorcycles.

Saheli Ezo 4T exceeds the international specifications of **API SL** and **JASO MA 2** for 4-stroke motorcycle oils and the requirements of leading global 4-stroke motorcycle manufacturers.

Saheli Ezo 4T is available in **SAE 10W30, SAE 10W40, 20W40** and **SAE 20W50** grades.

Features and Benefits

- Excellent anti-wear properties protect vital engine and gear components leading to reduced maintenance costs.
- Good thermo-oxidative stability prevents harmful deposit formation and controls oil thickening facilitating extended engine and oil life.
- Controlled frictional properties eliminate clutch slippage and improve drivability.
- Better detergency/dispersancy keeps engine cleaner and reduces maintenance costs.
- Effective rust and corrosion inhibition property ensures longer life of critical engine components.

Applications

- Recommended for air-cooled 4-stroke motorcycle engines where **API SL** and **JASO MA 2** quality oil is required.
- Also suitable for small 4-stroke gasoline engines used in portable generators, pumps, garden machinery and other applications.

Specifications

Meets:

- **API SL, JASO MA2**

Test Parameters	Test Method	Typical Results			
		20W50	20W40	10W40	10W30
SAE Viscosity Grade					
Density @ 15°C gm/cm ³	ASTM D1298	0.890	0.889	0.8784	0.8786
Viscosity Index	ASTM D2270	120	115	122	128
Viscosity @ 100°C (cSt)	ASTM D 445	19.30	14.53	13.87	11.68
Pour Point °C	ASTM D 97	-21	-30	-24	-18
Flash Point (COC) °C	ASTM D 92	248	230	236	228
T.B.N mg KOH/gm	ASTM D 2896	7.35	7.5	9.6	8.5
Sulphated Ash, %wt	ASTMD 874	1.08	1.08	0.98	0.98

The information contained in this data sheet are indicative and correspond to the date of publication of this document. The above data are based on laboratory tests. It is the reader's interest to ensure whether the most recent version of the data sheet. A safety data sheet is available on request by our sales consultant. For more information, please contact the sales department.

Saheli Energy Solutions P.O.Box : 500102 Fax : +971 44301710 Dubai, UAE - info@saheli-lubes.com - www.saheli-lubes.com