

Product Data Sheet

Premium GT

Description and Applications

Saheli Premium GT is high quality passenger car motor oil designed for older turbocharged and naturally aspirated gasoline powered passenger cars and diesel powered light duty vehicles. It is blended using selected premium quality base oils and performance additives to provide excellent engine protection.

Saheli Premium GT is developed to exceed the performance requirements of API (American Petroleum Institute) **SG/CF/CD** and is available in three viscosity grades viz. **SAE 10W30, SAE 15W40 and SAE 20W50.**

Features and Benefits

- Better thermo-oxidative stability minimizes deposits and sludge build-up
- Effective rust inhibitors retard formation of rust in critical engine parts
- Advanced anti-wear technology minimizes engine wear and thereby reduce maintenance cost
- Good Stay-in-grade performance ensures reliable lubrication even at higher load and operating temperatures

Applications

- Recommended for use in all modern high performance turbocharged and naturally aspirated gasoline powered passenger cars and diesel powered light duty vehicles requiring API SG and API CF/CD quality oils
- It may also be used in older vehicles where an API service category SF or commercial category CC quality oil is recommended

Specifications

Meets:

- **API SG/CF/CD**

Test Parameters	Test Method	Typical Results		
		10W30	15W40	20W50
SAE Viscosity Grade		10W30	15W40	20W50
Density @ 15°C gm/cm ³	ASTM D1298	0.898	0.899	0.899
Viscosity Index	ASTM D2270	140	138	125
Viscosity @ 100°C (cSt)	ASTM D 445	10.9	14.30	19.00
Pour Point °C	ASTM D 97	-33	-27	-24
Flash Point (COC) °C	ASTM D 92	226	220	234
T.B.N mg KOH/gm	ASTM D 2896	5.70	5.70	5.70
Sulphated Ash w%	ASTM D 874	0.68	0.68	0.68

The information contained in this data sheet are indicative and correspond to the date of publication of this document. The above data are based on laboratory tests. It is the reader's interest to ensure whether the most recent version of the data sheet. A safety data sheet is available on request by our sales consultant. For more information, please contact the sales department.

Saheli Energy Solutions P.O.Box : 500102 Fax : +971 44301710 Dubai, UAE - info@saheli-lubes.com - www.saheli-lubes.com